

Package ‘BayesBP’

October 12, 2022

Type Package

Title Bayesian Estimation using Bernstein Polynomial Fits Rate Matrix

Version 1.1

Author Li-Syuan Hong [aut, cre]

Maintainer Li-Syuan Hong <lisyuan@nhri.org.tw>

Description Smoothed lexis diagrams with Bayesian method specifically tailored to cancer incidence data. Providing to calculating slope and constructing credible interval.
LC Chien et al. (2015) <[doi:10.1080/01621459.2015.1042106](https://doi.org/10.1080/01621459.2015.1042106)>.
LH Chien et al. (2017) <[doi:10.1002/cam4.1102](https://doi.org/10.1002/cam4.1102)>.

License GPL (>= 2)

Encoding UTF-8

Date 2020-08-17

LazyLoad yes

LazyData yes

Depends R (>= 3.5.0),parallel,iterators,utils,stats,openxlsx

RoxygenNote 7.1.1

Suggests testthat (>= 2.1.0)

NeedsCompilation no

Repository CRAN

Date/Publication 2020-08-27 09:30:03 UTC

R topics documented:

bin	2
BP2D	2
BP2D_coef	5
BP2D_table	5
BPbasis	6
BPFhat	7
Credible_interval	7

gen_data	8
M	9
PD_BPbasis	9
PD_BPFhat	10
PD_Credible_interval	11
Rhat	11
scale_to_01	12
simulated_data_1	12
simulated_data_2	13
write.BP	13
write.BPtable	14

Index	15
--------------	-----------

bin	<i>Binomial function</i>
-----	--------------------------

Description

Binomial function

Usage

bin(n, i, x)

Arguments

n	Integer.
i	Integer($i < n$).
x	Numeric($0 \leq x \leq 1$).

Examples

bin(5,3, .5)

BP2D	<i>Bayesian estimation using two dimensions Bernstein polynomial</i>
------	--

Description

This function runs Metropolis-Hasting algorithm which is given setting prior and data. This algorithm starts storing coefficients when it runs halfway, so we use second halves of coefficients compute Rhat to check convergence.

Usage

```
BP2D(
  prior,
  ages,
  years,
  disease,
  population,
  Iterations = 2e+05,
  n_chain = 5,
  n_cluster = 1,
  nn = 2,
  interval = 100,
  RJC = 0.35,
  seed = TRUE,
  set = 1,
  double = 4
)
```

Arguments

prior	prior=(n0,alpha,L) where alpha is a Poisson parameter,n0 is upper bound of alpha L can be every number which is bigger than one.
ages	Range of ages.
years	Range of years.
disease	Disease matrix.
population	Population matrix.
Iterations	Iterations of chain.
n_chain	Number of Markov chain.
n_cluster	This parameter means number of cores, five cores is recommended.(default: n_cluster=1).
nn	The parameter nn is lower bound of alpha.
interval	Each hundreds save one coefficient.
RJC	Control parameter for transfer dimension.
seed	Set seed yes or not.
set	Choose seed.(defaults:set=1)
double	If R.hat >1.1 then double the iterations of times.

Value

This function will return Bayesian estimate of incidence,Stored parameters,posterior mean,posterior max and table.

Fhat	Bayesian estimate of incidence.
chain	Bayesian estimate of posterior p-value mean.

maxchain Bayesian estimate of posterior p-value max.
store_coefficients Two dimensional Bernstein coefficients.
output When M-H algorithm ends,construct the table which contains norm,mean of Fhat,maximum of Fhat,R.hat,iterations,P-value and elapsed time.

References

Li-Chu Chien,Yuh-Jenn Wu,Chao A. Hsiung,Lu-Hai Wang,I-Shou Chang(2015).Smoothed Lexis Diagrams With Applications to Lung and Breast Cancer Trends in Taiwan,Journal of the American Statistical Association, Taylor & Francis Journals, vol. 110(511), pages 1000-1012, September.

See Also

Other Bayesain estimate: [BP2D_coef\(\)](#), [BP2D_table\(\)](#)

Examples

```
# ----- #
library(BayesBP)
ages<-35:85
years<-1988:2007
prior<-c(10,5,2)
data(simulated_data_1)
disease<-simulated_data_1$disease
population<-simulated_data_1$population
result<-BP2D(prior,ages,years,disease,population)
# ----- #
# Bernstein basis
basis<-BPbasis(ages,years,10)
pdbasis1<-PD_BPbasis(ages,years,10,by = 1)
pdbasis2<-PD_BPbasis(ages,years,10,by = 2)
# Bernstein polynomial
coef<-result$store_coefficients$chain_1[[1]]
BPFhat(coef,ages,years,basis)
PD_BPFhat(coef,ages,years,pdbasis1,by = 1)
PD_BPFhat(coef,ages,years,pdbasis2,by = 2)
# Credible interval
Credible_interval(result)
PD_Credible_interval(result,by = 1)
PD_Credible_interval(result,by = 2)
# ----- #
# Given four prior set
ages<-35:85
years<-1988:2007
data(simulated_data_2)
disease<-simulated_data_2$disease
population<-simulated_data_2$population
p<-expand.grid(n0=c(10,20),alpha=c(5,10),LL=c(2,4))
prior_set<-p[p$n0==p$alpha*2,]
```

```

result_list<-paste0('result',1:nrow(prior_set))
for (i in seq_len(nrow(prior_set))) {
  prior<-prior_set[i,]
  assign(result_list[i],BP2D(prior,ages,years,disease,population))
  write.BP(get(result_list[i]),sprintf('%s.xlsx',result_list[i]))
}
tab<-BP2D_table(result_list)
write.BPtable(tab,'result_table.xlsx')
# ----- #

```

BP2D_coef	<i>Getting coefficeint from BP2D result.</i>
-----------	--

Description

This function will return coefficient and length of each set of coefficeint.

Usage

```
BP2D_coef(result)
```

Arguments

result This is output of BP2D.

Value

Coefficients table.

See Also

Other Bayesain estimate: [BP2D_table\(\)](#), [BP2D\(\)](#)

BP2D_table	<i>Table and Criterion.</i>
------------	-----------------------------

Description

If you give more groups of prior,you can use this function to get the table and T criterion.

Usage

```
BP2D_table(results_list)
```

Arguments

results_list A vector of characters.

Value

Table and criterion T.

See Also

Other Bayesian estimate: [BP2D_coef\(\)](#), [BP2D\(\)](#)

BPbasis

Bernstein polynomial basis.

Description

This function build two dimensional Bernstein polynomial basis.

Usage

```
BPbasis(ages, years, n0, N = 1)
```

Arguments

ages	Range of ages.
years	Range of years.
n0	Upper bound of poisson random variable.
N	Lower bound of poisson random variable.

Value

Bernstein basis.

See Also

Other Bernstein basis: [PD_BPbasis\(\)](#)

Examples

```
ages <- 35:85
years <- 1988:2007
list.basis <- BPbasis(ages, years, 10)
list.basis
```

BPFhat	<i>Two dimensional Bernstein polynomial</i>
--------	---

Description

Given Bernstein polynomial coefficients to compute Fhat.

Usage

```
BPFhat(coef, ages, years, basis)
```

Arguments

coef	Bernstein polynomial coefficients.
ages	Range of ages.
years	Range of years.
basis	Bernstein polynomial basis.

Value

This function return outer Bernstein polynomial using coefficients.

See Also

Other outer Bernstein polynomial: [PD_BPFhat\(\)](#)

Examples

```
coef <- runif(9)
ages <- 35:85
years <- 1988:2007
list.basis <- BPbasis(ages,years,10)
BPFhat(coef,ages,years,list.basis)
```

Credible_interval	<i>Credible interval.</i>
-------------------	---------------------------

Description

Building two dimensional Bernstein polynomial credible interval.

Usage

```
Credible_interval(result, n_cluster = 1, alpha = 0.05)
```

Arguments

result	This is output of BP2D.
n_cluster	Muticores is remmended.(default:n_cluster=1)
alpha	Level of significance.

Value

Bayesian credible interval with level of significance.

References

L.H. Chien, T.J. Tseng, C.H. Chen, H.F. Jiang, F.Y. Tsai, T.W. Liu, C.A. Hsiung, I.S. Chang Comparison of annual percentage change in breast cancer incidence rate between Taiwan and the United States-A smoothed Lexis diagram approach.

See Also

Other Credible interval: [PD_Credibile_interval\(\)](#)

gen_data

Generated data

Description

Generated data

Usage

```
gen_data(ages, years, FT, M)
```

Arguments

ages	Ages.
years	Years.
FT	Rate function.
M	Population function.

M	<i>Risky population function</i>
---	----------------------------------

Description

Risky population function

Usage

$M(x, y)$

Arguments

x	Numeric.
y	Numeric.

PD_BPbasis	<i>Partial differential Bernstein polynomial basis.</i>
------------	---

Description

This function build two dimensional Bernstein polynomial basis.

Usage

PD_BPbasis(ages, years, n0, N = 1, by = 1)

Arguments

ages	Range of ages.
years	Range of years.
n0	Upper bound of possion random variable.
N	Lower bound of possion random variable.
by	1: partial differential by ages; 2: partial differential by years.

Value

Partial differential Bernstein basis.

See Also

Other Bernstein basis: [BPbasis\(\)](#)

Examples

```
ages <- 35:85
years <- 1988:2007
pdbasis <- PD_BPbasis(ages,years,10,by = 1)
pdbasis
```

PD_BPFhat

Two dimensional Bernstein polynomial

Description

Given Bernstein polynomial coefficients to compute Fhat.

Usage

```
PD_BPFhat(coef, ages, years, pdbasis, by = 1)
```

Arguments

coef	Bernstein polynomial coefficients.
ages	Range of ages.
years	Range of years.
pdbasis	Partial differential Bernstein polynomial basis.
by	1: partial differential by ages; 2: partial differential by years.

Value

Partial differential Bernstein polynomial given coefficients.

See Also

Other outer Bernstein polynomial: [BPFhat\(\)](#)

Examples

```
coef <- runif(9)
ages <- 35:85
years <- 1988:2007
pdbasis <- PD_BPbasis(ages,years,10,N=1,by=1)
PD_BPFhat(coef,ages,years,pdbasis,by=1)
```

PD_Credibile_interval *Credibile interval.*

Description

Building two dimensional Bernstein polynomial credible interval.

Usage

```
PD_Credibile_interval(result, n_cluster = 1, alpha = 0.05, by = 1)
```

Arguments

result	This is output of BP2D.
n_cluster	Muticores is remmended.(default:n_cluster=1)
alpha	Level of significance.
by	1: partial differential by ages; 2: partial differential by years.

Value

Bayesian credible interval with level of significance.

References

L.H. Chien, T.J. Tseng, C.H. Chen, H.F. Jiang, F.Y. Tsai, T.W. Liu, C.A. Hsiung, I.S. Chang Comparison of annual percentage change in breast cancer incidence rate between Taiwan and the United States-A smoothed Lexis diagram approach.

See Also

Other Credibile interval: [Credibile_interval\(\)](#)

Rhat *Gelman Rubin statistics.*

Description

Check Markov chains for convergence.

Usage

```
Rhat(M, burn.in = 0.5)
```

Arguments

M	An n x m numeric matrix of Markov Chains.
burn.in	The default value 0.5 means that the second halves of chains will be used to compute.

Value

Gelman Rubin statistics.

References

Gelman A., Carlin J.B., Stern H.S., and Rubin D.B. (2004), Bayesian Data Analysis, Boca Raton, FL: Chapman & Hall/CRC.

scale_to_01	<i>Scale to [0,1]</i>
-------------	-----------------------

Description

Scale to [0,1]

Usage

```
scale_to_01(x)
```

Arguments

x	Vector.
---	---------

Examples

```
scale_to_01(35:85)
(35:85-35)/(85-35)
scale_to_01(runif(10))
```

simulated_data_1	<i>Generate simulated data 1</i>
------------------	----------------------------------

Description

Given rate function 1 generated data.

Usage

```
data(simulated_data_1)
```

Format

list of matrix

Examples

```
ages <- 35:85
years <- 1988:2007
FT1 <- function(x,y){0.00148*sin(0.5*pi*x*y)+0.00002}
simulated_data_1 <- gen_data(ages,years,FT1,M)
```

simulated_data_2 *Generate simulated data 2*

Description

Given rate function 2 generated data.

Usage

```
data(simulated_data_2)
```

Format

list of matrix

Examples

```
ages <- 35:85
years <- 1988:2007
FT2 <- function(x,y){0.00148*sin(0.5*pi*x*(y+0.2))+0.00002}
simulated_data_2 <- gen_data(ages,years,FT2,M)
```

write.BP *Write xlsx file*

Description

This function will write result of BP2D to xlsx file.

Usage

```
write.BP(writedata, filename)
```

Arguments

writedata result of BP2D(character or list).
filename xlsx file name.

write.BPtable	<i>Write BPtable as xlsx file</i>
---------------	-----------------------------------

Description

If your environment has some result of BP2D, then you can use this function to store BPtable.

Usage

```
write.BPtable(BPtable, filename)
```

Arguments

BPtable	output of BP2D_table.
filename	xlsx file name.

Index

* **Bayesian estimate**

BP2D, 2
BP2D_coef, 5
BP2D_table, 5

* **Bernstein basis**

BPbasis, 6
PD_BPbasis, 9

* **Credible interval**

Credible_interval, 7
PD_Credible_interval, 11

* **datasets**

gen_data, 8
M, 9
simulated_data_1, 12
simulated_data_2, 13

* **outer Bernstein polynomial**

BPFhat, 7
PD_BPFhat, 10

bin, 2
BP2D, 2, 5, 6
BP2D_coef, 4, 5, 6
BP2D_table, 4, 5, 5
BPbasis, 6, 9
BPFhat, 7, 10

Credible_interval, 7, 11

gen_data, 8

M, 9

PD_BPbasis, 6, 9
PD_BPFhat, 7, 10
PD_Credible_interval, 8, 11

Rhat, 11

scale_to_01, 12
simulated_data_1, 12
simulated_data_2, 13

write.BP, 13
write.BPtable, 14