

Package ‘PopGenHelpR’

July 2, 2025

Title Streamline Population Genomic and Genetic Analyses

Version 1.4.0

Description Estimate commonly used population genomic statistics and generate publication quality figures. 'PopGenHelpR' uses vcf, 'geno' (012), and csv files to generate output.

URL <https://kfarleigh.github.io/PopGenHelpR/>

BugReports <https://github.com/kfarleigh/PopGenHelpR/issues>

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.2

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

Imports dplyr, ggplot2, magrittr, methods, reshape2, rlang, scatterpie, stats, geodata, terra, ggspatial, spdep, sf, utils, vcfR

Depends R (>= 2.10)

LazyData true

VignetteBuilder knitr

NeedsCompilation no

Author Keaka Farleigh [aut, cph, cre] (ORCID: <https://orcid.org/0000-0002-9195-121X>),
Mason Murphy [aut, cph, ctb] (ORCID: <https://orcid.org/0000-0002-5317-1386>),
Christopher Blair [aut, cph, ctb] (ORCID: <https://orcid.org/0000-0002-4782-6788>),
Tereza Jezkova [aut, cph, ctb] (ORCID: <https://orcid.org/0000-0003-4114-4564>)

Maintainer Keaka Farleigh <keakafarleigh@gmail.com>

Repository CRAN

Date/Publication 2025-07-02 19:00:02 UTC

Contents

Ancestry_barchart	2
Differentiation	3
Fst_dat	5
Heterozygosity	6
Het_dat	8
HornedLizard_Pop	9
HornedLizard_VCF	10
Network_map	10
Pairwise_heatmap	13
PCA	14
Piechart_map	15
Plot_coordinates	18
Point_map	20
Private.alleles	23
Q_dat	24
Index	26

Ancestry_barchart	<i>Plot an ancestry matrix for individuals and(or) populations.</i>
-------------------	---

Description

Plot an ancestry matrix for individuals and(or) populations.

Usage

```
Ancestry_barchart(
  anc.mat,
  pops,
  K,
  plot.type = "all",
  col,
  ind.order = NULL,
  pop.order = NULL,
  legend_pos = "right"
)
```

Arguments

anc.mat	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. The first column should be the names of each sample/population, followed by the estimated contribution of each cluster to that individual/pop.
---------	--

pops	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. The first two columns should indicate the sample name (first column) and the population that sample belongs to (second column). Other columns (i.e., latitude, longitude) can be present, but will not be used.
K	Numeric. The number of genetic clusters in your data set, please contact the package authors if you need help doing this.
plot.type	Character string. Options are all, individual, and population. All is default and recommended, this will plot a barchart for both the individuals and populations.
col	Character vector indicating the colors you wish to use for plotting.
ind.order	Character vector indicating the order to plot the individuals in the individual ancestry bar chart.
pop.order	Character vector indicating the order to plot the populations in the population ancestry bar chart.
legend_pos	Character. The desired position of the legend. The default is "none", which removes the legend. Other options include "left", "right", "top" or "bottom". Please see the ggplot2 documentation for all of the legend placement options.

Value

A list containing your plots and the data frames used to generate the plots.

Author(s)

Keaka Farleigh

Examples

```
data(Q_dat)
Qmat <- Q_dat[[1]]
rownames(Qmat) <- Qmat[,1]
Loc <- Q_dat[[2]]
Test_all <- Ancestry_barchart(anc.mat = Qmat, pops = Loc, K = 5,
plot.type = 'all', col = c('#d73027', '#fc8d59', '#e0f3f8', '#91bfdb', '#4575b4'))
```

Differentiation	<i>A function to estimate three measures of genetic differentiation using geno files, vcf files, or vcfR objects. Data is assumed to be bi-allelic.</i>
-----------------	---

Description

A function to estimate three measures of genetic differentiation using geno files, vcf files, or vcfR objects. Data is assumed to be bi-allelic.

Usage

```
Differentiation(
  data,
  pops,
  statistic = "all",
  missing_value = NA,
  write = FALSE,
  prefix = NULL,
  population_col = NULL,
  individual_col = NULL
)
```

Arguments

<code>data</code>	Character. String indicating the name of the vcf file, geno file or vcfR object to be used in the analysis. The genotypes within the vcf should be separated by a "/" or " ". This normally indicates unphased and phased genotypes, respectively. Please reach out to PopGenHelpR authors if you have questions.
<code>pops</code>	Character. String indicating the name of the population assignment file or dataframe containing the population assignment information for each individual in the data. This file must be in the same order as the vcf file and include columns specifying the individual and the population that individual belongs to. The first column should contain individual names and the second column should indicate the population assignment of each individual. Alternatively, you can indicate the column containing the individual and population information using the <code>individual_col</code> and <code>population_col</code> arguments.
<code>statistic</code>	Character. String or vector indicating the statistic to calculate. Options are any of: <code>all</code> ; all of the statistics; <code>Fst</code> , Weir and Cockerham (1984) <code>Fst</code> ; <code>NeisD</code> , Nei's D statistic; <code>JostsD</code> , Jost's D.
<code>missing_value</code>	Character. String indicating missing data in the input data. It is assumed to be <code>NA</code> , but that may not be true (is likely not) in the case of geno files.
<code>write</code>	Boolean. Whether or not to write the output to files in the current working directory. There will be one or two files for each statistic. Files will be named based on their statistic such as <code>Fst_perpop.csv</code> .
<code>prefix</code>	Character. Optional argument. String that will be appended to file output. Please provide a prefix if <code>write</code> is set to <code>TRUE</code> .
<code>population_col</code>	Numeric. Optional argument (a number) indicating the column that contains the population assignment information.
<code>individual_col</code>	Numeric. Optional argument (a number) indicating the column that contains the individuals (i.e., sample name) in the data.

Value

A list containing the estimated heterozygosity statistics. The per pop values are calculated by taking the average of the per locus estimates.

Author(s)

Keaka Farleigh

References**Fst:**

Pembleton, L. W., Cogan, N. O., & Forster, J. W. (2013). StAMPP: An R package for calculation of genetic differentiation and structure of mixed-ploidy level populations. *Molecular ecology resources*, 13(5), 946-952.[doi:10.1111/17550998.12129](https://doi.org/10.1111/17550998.12129)

Weir, B. S., & Cockerham, C. C. (1984). Estimating F-statistics for the analysis of population structure. *evolution*, 1358-1370.

Nei's D:

Nei, M. (1972). Genetic distance between populations. *The American Naturalist*, 106(949), 283-292.[doi:10.1086/282771](https://doi.org/10.1086/282771)

[doi:10.1111/17550998.12129](https://doi.org/10.1111/17550998.12129) Pembleton, L. W., Cogan, N. O., & Forster, J. W. (2013). StAMPP: An R package for calculation of genetic differentiation and structure of mixed-ploidy level populations. *Molecular ecology resources*, 13(5), 946-952.

Jost's D:

Jost L (2008). GST and its relatives do not measure differentiation. *Molecular Ecology*, 17, 4015–4026.[doi:10.1111/j.1365294X.2008.03887.x](https://doi.org/10.1111/j.1365294X.2008.03887.x)

Examples

```
data("HornedLizard_Pop")
data("HornedLizard_VCF")
Test <- Differentiation(data = HornedLizard_VCF, pops = HornedLizard_Pop, write = FALSE)
```

Fst_dat	<i>A genetic differentiation matrix and locality information for each population. This data was generated by subsetting data of Farleigh et al., 2021.</i>
---------	--

Description

A symmetric matrix with estimated genetic differentiation (Fst) between 3 populations.

Usage

```
data(Fst_dat)
```

Format

A list with two elements:

Fst_dat Data frame with three rows and three columns

Loc_dat Data frame containing the locality information for each population

...

Source

Farleigh, K., Vladimirova, S. A., Blair, C., Bracken, J. T., Koochekian, N., Schield, D. R., ... & Jezkova, T. (2021). The effects of climate and demographic history in shaping genomic variation across populations of the Desert Horned Lizard (*Phrynosoma platyrhinos*). *Molecular Ecology*, 30(18), 4481-4496.

Examples

```
data(Fst_dat)
Fst <- Fst_dat[[1]]
Loc <- Fst_dat[[2]]

Test <- Network_map(dat = Fst, pops = Loc,
neighbors = 2,col = c('#4575b4', '#91bfd8', '#e0f3f8', '#fd8d3c', '#fc4e2a'),
statistic = "Fst", Lat_buffer = 1, Long_buffer = 1)

Fstat_plot <- Pairwise_heatmap(dat = Fst, statistic = 'FST')
```

Heterozygosity	<i>A function to estimate seven measures of heterozygosity using geno files, vcf files, or vcfR objects. Data is assumed to be bi-allelic.</i>
----------------	--

Description

A function to estimate seven measures of heterozygosity using geno files, vcf files, or vcfR objects. Data is assumed to be bi-allelic.

Usage

```
Heterozygosity(
  data,
  pops,
  statistic = "all",
  missing_value = NA,
  write = FALSE,
  prefix = NULL,
  population_col = NULL,
  individual_col = NULL
)
```

Arguments

data	Character. String indicating the name of the vcf file, geno file or vcfR object to be used in the analysis.
------	---

pops	Character. String indicating the name of the population assignment file or dataframe containing the population assignment information for each individual in the data. This file must be in the same order as the vcf file and include columns specifying the individual and the population that individual belongs to. The first column should contain individual names and the second column should indicate the population assignment of each individual. Alternatively, you can indicate the column containing the individual and population information using the individual_col and population_col arguments.
statistic	Character. String or vector indicating the statistic to calculate. Options are any of: all; all of the statistics; Ho, observed heterozygosity; He, expected heterozygosity; PHt, proportion of heterozygous loci; Hs_exp, heterozygosity standardized by the average expected heterozygosity; Hs_obs, heterozygosity standardized by the average observed heterozygosity; IR, internal relatedness; HL, homozygosity by locus.
missing_value	Character. String indicating missing data in the input data. It is assumed to be NA, but that may not be true (is likely not) in the case of geno files.
write	Boolean. Whether or not to write the output to files in the current working directory. There will be one or two files for each statistic. Files will be named based on their statistic such as Ho_perpop.csv or Ho_perloc.csv.
prefix	Character. Optional argument. String that will be appended to file output. Please provide a prefix if write is set to TRUE.
population_col	Numeric. Optional argument (a number) indicating the column that contains the population assignment information.
individual_col	Numeric. Optional argument (a number) indicating the column that contains the individuals (i.e., sample name) in the data.

Value

A list containing the estimated heterozygosity statistics. The per pop values are calculated by taking the average of the per locus estimates.

Author(s)

Keaka Farleigh

References

Expected (He) and observed heterozygosity (Ho):

Nei, M. (1987) *Molecular Evolutionary Genetics*. Columbia University Press

Homozygosity by locus (HL) and internal relatedness (IR):

Alho, J. S., Välimäki, K., & Merilä, J. (2010). Rhh: an R extension for estimating multilocus heterozygosity and heterozygosity–heterozygosity correlation. *Molecular ecology resources*, 10(4), 720–722.

Amos, W., Worthington Wilmer, J., Fullard, K., Burg, T. M., Croxall, J. P., Bloch, D., & Coulson, T. (2001). The influence of parental relatedness on reproductive success. *Proceedings of the Royal Society of London. Series B: Biological Sciences*, 268(1480), 2021–2027. doi:10.1098/rspb.2001.1751

Aparicio, J. M., Ortego, J., & Cordero, P. J. (2006). What should we weigh to estimate heterozygosity, alleles or loci?. *Molecular Ecology*, 15(14), 4659-4665.

Heterozygosity standardized by expected (Hs_exp) and observed heterozygosity (Hs_obs):

Coltman, D. W., Pilkington, J. G., Smith, J. A., & Pemberton, J. M. (1999). Parasite-mediated selection against Inbred Soay sheep in a free-living island population. *Evolution*, 53(4), 1259-1267.[doi:10.1111/j.15585646.1999.tb04538.x](https://doi.org/10.1111/j.15585646.1999.tb04538.x)

Examples

```
data("HornedLizard_Pop")
data("HornedLizard_VCF")
Test <- Heterozygosity(data = HornedLizard_VCF, pops = HornedLizard_Pop, write = FALSE)
```

Het_dat	<i>A data frame of hypothetical heterozygosity data produced by Heterozygosity.</i>
---------	---

Description

Data frame containing 5 columns and 3 rows

Usage

```
data(Het_dat)
```

Format

A data frame with 5 columns and 3 rows:

Heterozygosity Estimated heterozygosity

Pop Population assignment

Standard.Deviation standard deviation

Longitude Longitude

Latitude Latitude

...

Source

Coordinates and population names taken from Farleigh, K., Vladimirova, S. A., Blair, C., Bracken, J. T., Koochekian, N., Schield, D. R., ... & Jezkova, T. (2021). The effects of climate and demographic history in shaping genomic variation across populations of the Desert Horned Lizard (*Phrynosoma platyrhinos*). *Molecular Ecology*, 30(18), 4481-4496.

Examples

```
data(Het_dat)
Test <- Point_map(Het_dat, statistic = "Heterozygosity")
```

HornedLizard_Pop	<i>A population assignment data frame to be used in Heterozygosity and Differentiation.</i>
------------------	---

Description

Data frame containing 4 columns and 72 rows

Usage

```
data(HornedLizard_Pop)
```

Format

A data frame with 4 columns and 72 rows:

Sample Sample Name

Population Population assignment according to sNMF results (see citation)

Longitude Longitude

Latitude Latitude

...

Source

Coordinates and population names taken from Farleigh, K., Vladimirova, S. A., Blair, C., Bracken, J. T., Koochekian, N., Schield, D. R., ... & Jezkova, T. (2021). The effects of climate and demographic history in shaping genomic variation across populations of the Desert Horned Lizard (*Phrynosoma platyrhinos*). *Molecular Ecology*, 30(18), 4481-4496.

Examples

```
data("HornedLizard_Pop")
data("HornedLizard_VCF")
Test <- Differentiation(data = HornedLizard_VCF, pops = HornedLizard_Pop, write = FALSE)
```

HornedLizard_VCF	<i>A vcfR object to be used in Heterozygosity and Differentiation.</i>
------------------	--

Description

Data frame containing 4 columns and 72 rows

Usage

```
data(HornedLizard_Pop)
```

Format

A vcfR object

vcfR object A vcfR object containing genotype and sample information for 72 individuals.

...

Source

Farleigh, K., Vladimirova, S. A., Blair, C., Bracken, J. T., Koochekian, N., Schield, D. R., ... & Jezkova, T. (2021). The effects of climate and demographic history in shaping genomic variation across populations of the Desert Horned Lizard (*Phrynosoma platyrhinos*). *Molecular Ecology*, 30(18), 4481-4496.

Examples

```
data("HornedLizard_Pop")
data("HornedLizard_VCF")
Test <- Heterozygosity(data = HornedLizard_VCF, pops = HornedLizard_Pop, write = FALSE)
```

Network_map	<i>A function to map statistics (i.e., genetic differentiation) between points as a network on a map.</i>
-------------	---

Description

A function to map statistics (i.e., genetic differentiation) between points as a network on a map.

Usage

```

Network_map(
  dat,
  pops,
  neighbors,
  col,
  statistic = NULL,
  breaks = NULL,
  Lat_buffer = 1,
  Long_buffer = 1,
  Latitude_col = NULL,
  Longitude_col = NULL,
  country_code = NULL,
  shapefile = NULL,
  raster = NULL,
  legend_pos = "none",
  scale_bar = FALSE,
  north_arrow = FALSE,
  north_arrow_style = ggspatial::north_arrow_nautical(),
  north_arrow_position = NULL,
  shapefile_plot_position = NULL,
  raster_plot_position = NULL,
  shapefile_col = NULL,
  shapefile_outline_col = NULL,
  shp_outwidth = 1,
  raster_col = c("#2c7bb6", "#abd9e9", "#ffffbf", "#fdae61", "#d7191c"),
  interpolate_raster = NULL,
  raster_breaks = NULL,
  discrete_raster = NULL
)

```

Arguments

dat	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. If it is a csv, the 1st row should contain the individual/population names. The columns should also be named in this fashion.
pops	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. The columns should be named Sample, containing the sample IDs; Population indicating the population assignment of the individual; Long, indicating the longitude of the sample; Lat, indicating the latitude of the sample. Alternatively, see the Longitude_col and Latitude_col arguments.
neighbors	Numeric or character. The number of neighbors to plot connections with, or the specific relationship that you want to visualize. Names should match those in the population assignment file and be separated by an underscore. If I want to visualize the relationship between East and West, for example, I would set neighbors = "East_West".

col	Character vector indicating the colors you wish to use for plotting.
statistic	Character indicating the statistic being plotted. This will be used to title the legend. The legend title will be blank if left as NULL.
breaks	Numeric. The breaks used to generate the color ramp when plotting. The number of breaks should match the number of colors.
Lat_buffer	Numeric. A buffer to customize visualization.
Long_buffer	Numeric. A buffer to customize visualization.
Latitude_col	Numeric. The number of the column indicating the latitude for each sample. If this is not null, PopGenHelpR will use this column instead of looking for the Lat column.
Longitude_col	Numeric. The number of the column indicating the longitude for each sample. If this is not null, PopGenHelpR will use this column instead of looking for the Long column.
country_code	Character. A country code or vector of country codes from the R package geo-data specifying the country that you want to plot administrative borders for (e.g, US states). You can determine the correct codes using <code>geodata's country_codes</code> function.
shapefile	Character. A file name, vector of file names of a shapefile(s) to plot on the map, or a spatvector object that is compatible with the R package <code>terra</code> . This should be used in conjunction with the <code>shapefile_plot_position</code> argument.
raster	Character. A file name or a spatraster object that is compatible with the <code>terra</code> R package. This should be used in conjunction with the <code>raster_plot_position</code> argument.
legend_pos	Character. The desired position of the legend. The default is "none", which removes the legend. Other options include "left", "right", "top" or "bottom". Please see the <code>ggplot2</code> documentation for all of the legend placement options.
scale_bar	Boolean. Whether or not to add a scale bar. Note that maps with large areas or those that use unprojected spatial data (i.e., WGS 84) will generate a warning that the scale bar varies.
north_arrow	Boolean. Whether or not to add a north arrow.
north_arrow_style	Character. Which style of north arrow to add. See ggspatial documentation for more details.
north_arrow_position	Character. The position of the north arrow. See ggspatial documentation for more details.
shapefile_plot_position	Numeric. A number indicating which position to plot the shapefile in. The options are 1, which plots the shapefile on top of the base world map (under points and administrative boundaries), 2 which plots the shapefile on top of administrative boundaries (but under points), and 3, which plots the shapefile on top of everything.
raster_plot_position	Numeric. A number indicating which position to plot the shapefile in. The options are 1, which plots the raster on top of the base world map (under points

and administrative boundaries), 2 which plots the raster on top of administrative boundaries (but under points), and 3, which plots the raster on top of everything.

shapefile_col Character. A color or color vector indicating the color to fill the shapefile(s) with. Shapefiles will be colored alphabetically.

shapefile_outline_col Character. A color indicating the outline color of the shapefile.

shp_outwidth Numeric. The width of the shapefile outline.

raster_col Character. A character vector indicating the colors used to visualize the raster. The function will separate your raster data into the same number of bins as there are colors. If you provide 5 colors, for example, there will be 5 bins.

interpolate_raster Boolean. Whether or not to interpolate the raster. The default is to interpolate the raster.

raster_breaks Numeric or Character vector. Values to be used as breaks for the raster surface.

discrete_raster Boolean. Indicating whether or not the raster being supplied is discrete.

Value

A list containing the map and the matrix used to plot the map.

Author(s)

Keaka Farleigh

Examples

```
data(Fst_dat)
Fst <- Fst_dat[[1]]
Loc <- Fst_dat[[2]]
Test <- Network_map(dat = Fst, pops = Loc,
neighbors = 2,col = c('#4575b4', '#91bfd9', '#e0f3f8','#fd8d3c','#fc4e2a'),
statistic = "Fst", Lat_buffer = 1, Long_buffer = 1)
```

Pairwise_heatmap *A function to plot a heatmap from a symmetric matrix.*

Description

A function to plot a heatmap from a symmetric matrix.

Usage

```
Pairwise_heatmap(
  dat,
  statistic,
  col = c("#abd9e9", "#2c7bb6", "#ffffbf", "#fdae61", "#d7191c"),
  breaks = NULL
)
```

Arguments

<code>dat</code>	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. If it is a csv, the 1st row should contain the individual/population names. The columns should also be named in this fashion.
<code>statistic</code>	Character indicating the statistic represented in the matrix, this will be used to label the plot.
<code>col</code>	Character vector indicating the colors to be used in plotting. The vector should contain two colors, the first will be the low value, the second will be the high value.
<code>breaks</code>	Numeric. The breaks used to generate the color ramp when plotting. The number of breaks should match the number of colors.

Value

A heatmap plot

Examples

```
#' data(Fst_dat)
Fst <- Fst_dat[[1]]
Fstat_plot <- Pairwise_heatmap(dat = Fst, statistic = 'FST')
```

PCA

A function to perform principal component analysis (PCA) on genetic data. Loci with missing data will be removed prior to PCA.

Description

A function to perform principal component analysis (PCA) on genetic data. Loci with missing data will be removed prior to PCA.

Usage

```
PCA(
  data,
  center = TRUE,
  scale = FALSE,
  missing_value = NA,
  write = FALSE,
  prefix = NULL
)
```

Arguments

data	Character. String indicating the name of the vcf file, geno file or vcfR object to be used in the analysis.
center	Boolean. Whether or not to center the data before principal component analysis.
scale	Boolean. Whether or not to scale the data before principal component analysis.
missing_value	Character. String indicating missing data in the input data. It is assumed to be NA, but that may not be true (is likely not) in the case of geno files.
write	Boolean. Whether or not to write the output to files in the current working directory. There will be two files, one for the individual loadings and the other for the percent variance explained by each axis.
prefix	Character. Optional argument. String that will be appended to file output. Please provide a prefix if write is set to TRUE.

Value

A list containing two elements: the loadings of individuals on each principal component and the variance explained by each principal component.

Author(s)

Keaka Farleigh

Examples

```
data("HornedLizard_VCF")
Test <- PCA(data = HornedLizard_VCF)
```

Piechart_map	<i>Plot a map of ancestry pie charts.</i>
--------------	---

Description

Plot a map of ancestry pie charts.

Usage

```
Piechart_map(
  anc.mat,
  pops,
  K,
  plot.type = "all",
  col,
  piesize = 0.35,
  Lat_buffer,
  Long_buffer,
  Latitude_col = NULL,
```

```

Longitude_col = NULL,
country_code = NULL,
shapefile = NULL,
legend_pos = "none",
scale_bar = FALSE,
north_arrow = FALSE,
north_arrow_style = ggspatial::north_arrow_nautical(),
north_arrow_position = NULL,
shapefile_plot_position = NULL,
shapefile_col = NULL,
shapefile_outline_col = NULL,
shp_outwidth = 1
)

```

Arguments

anc.mat	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. The first column should be the names of each sample/population, followed by the estimated contribution of each cluster to that individual/pop.
pops	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. The columns should be named Sample, containing the sample IDs; Population indicating the population assignment of the individual, population and sample names must be the same type (i.e., both numeric or both characters); Long, indicating the longitude of the sample; Lat, indicating the latitude of the sample. Alternatively, see the Longitude_col and Latitude_col arguments.
K	Numeric. The number of genetic clusters in your data set, please contact the package authors if you need help doing this.
plot.type	Character string. Options are all, individual, and population. All is default and recommended, this will plot a piechart map for both the individuals and populations.
col	Character vector indicating the colors you wish to use for plotting.
piesize	Numeric. The radius of the pie chart for ancestry mapping.
Lat_buffer	Numeric. A buffer to customize visualization.
Long_buffer	Numeric. A buffer to customize visualization.
Latitude_col	Numeric. The number of the column indicating the latitude for each sample. If this is not null, PopGenHelpR will use this column instead of looking for the Lat column.
Longitude_col	Numeric. The number of the column indicating the longitude for each sample. If this is not null, PopGenHelpR will use this column instead of looking for the Long column.
country_code	Character. A country code or vector of country codes from the R package geodata specifying the country that you want to plot administrative borders for (e.g, US states). You can determine the correct codes using geodata's country_codes function.

shapefile	Character. A file name, vector of file names of a shapefile(s) to plot on the map, or a spatvector object that is compatible with the R package terra. This should be used in conjunction with the shapefile_plot_position argument.
legend_pos	Character. The desired position of the legend. The default is "none", which removes the legend. Other options include "left", "right", "top" or "bottom". Please see the ggplot2 documentation for all of the legend placement options.
scale_bar	Boolean. Whether or not to add a scale bar. Note that maps with large areas or those that use unprojected spatial data (i.e., WGS 84) will generate a warning that the scale bar varies.
north_arrow	Boolean. Whether or not to add a north arrow.
north_arrow_style	Character. Which style of north arrow to add. See ggspatial documentation for more details.
north_arrow_position	Character. The position of the north arrow. See ggspatial documentation for more details.
shapefile_plot_position	Numeric. A number indicating which position to plot the shapefile in. The options are 1, which plots the shapefile on top of the base world map (under points and administrative boundaries), 2 which plots the shapefile on top of administrative boundaries (but under points), and 3, which plots the shapefile on top of everything.
shapefile_col	Character. A color or color vector indicating the color to fill the shapefile(s) with. Similar to group_col, shapefiles will be colored alphabetically.
shapefile_outline_col	Character. A color indicating the outline color of the shapefile.
shp_outwidth	Numeric. The width of the shapefile outline.

Value

A list containing your plots and the data frames used to generate the plots.

Author(s)

Keaka Farleigh

Examples

```
data(Q_dat)
Qmat <- Q_dat[[1]]
rownames(Qmat) <- Qmat[,1]
Loc <- Q_dat[[2]]
Test_all <- Piechart_map(anc.mat = Qmat, pops = Loc, K = 5,
plot.type = 'all', col = c('#d73027', '#fc8d59', '#e0f3f8', '#91bfdb', '#4575b4'), piesize = 0.35,
Lat_buffer = 1, Long_buffer = 1)
```

Plot_coordinates *A function to plot coordinates on a map.*

Description

A function to plot coordinates on a map.

Usage

```
Plot_coordinates(  
  dat,  
  col = c("#A9A9A9", "#000000"),  
  size = 3,  
  Lat_buffer = 1,  
  Long_buffer = 1,  
  Latitude_col = NULL,  
  Longitude_col = NULL,  
  group = NULL,  
  group_col = NULL,  
  country_code = NULL,  
  shapefile = NULL,  
  raster = NULL,  
  legend_pos = "none",  
  scale_bar = FALSE,  
  north_arrow = FALSE,  
  north_arrow_style = ggspatial::north_arrow_nautical(),  
  north_arrow_position = NULL,  
  shapefile_plot_position = NULL,  
  raster_plot_position = NULL,  
  shapefile_col = NULL,  
  shapefile_outline_col = NULL,  
  shp_outwidth = 1,  
  raster_col = c("#2c7bb6", "#abd9e9", "#ffffbf", "#fdae61", "#d7191c"),  
  interpolate_raster = NULL,  
  raster_breaks = NULL,  
  discrete_raster = NULL  
)
```

Arguments

dat	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. The coordinates of each row should be indicated by columns named Longitude and Latitude. Alternatively, see the Latitude_col and Longitude_col arguments.
col	Character vector indicating the colors you wish to use for plotting, two colors are allowed. The first color will be the fill color, the second is the outline color.

	For example, if I want red points with a black outline I would set col to col = c("#FF0000", "#000000").
size	Numeric. The size of the points to plot.
Lat_buffer	Numeric. A buffer to customize visualization. This results in extra space in your map, so that your points are not cut off and so that the whole world is not plotted.
Long_buffer	Numeric. A buffer to customize visualization. This results in extra space in your map, so that your points are not cut off and so that the whole world is not plotted.
Latitude_col	Numeric. The number of the column indicating the latitude for each sample. If this is not null, PopGenHelpR will use this column instead of looking for the Latitude column.
Longitude_col	Numeric. The number of the column indicating the longitude for each sample. If this is not null, PopGenHelpR will use this column instead of looking for the Longitude column.
group	Character. The group that each point belongs to; this could be a species, population, etc. This is used in conjunction with the group_col parameter to fill each point in the group the same color.
group_col	Character. A color or color vector indicating the color to fill each point with on the map. The groups will be colored in alphabetical order. If your group_col = c("red", "blue", "purple") and groups = c("B", "C", "A"), for example the points from group A will be red, group B will be blue and group C will be purple.
country_code	Character. A country code or vector of country codes from the R package geo-data specifying the country that you want to plot administrative borders for (e.g, US states). You can determine the correct codes using geodata's country_codes function.
shapefile	Character. A file name, vector of file names of a shapefile(s) to plot on the map, or a spatvector object that is compatible with the R package terra. This should be used in conjunction with the shapefile_plot_position argument.
raster	Character. A file name or a spatraster object that is compatible with the terra R package. This should be used in conjunction with the raster_plot_position argument.
legend_pos	Character. The desired position of the legend. The default is "none", which removes the legend. Other options include "left", "right", "top" or "bottom". Please see the ggplot2 documentation for all of the legend placement options.
scale_bar	Boolean. Whether or not to add a scale bar. Note that maps with large areas or those that use unprojected spatial data (i.e., WGS 84) will generate a warning that the scale bar varies.
north_arrow	Boolean. Whether or not to add a north arrow.
north_arrow_style	Character. Which style of north arrow to add. See ggspatial documentation for more details.
north_arrow_position	Character. The position of the north arrow. See ggspatial documentation for more details.

shapefile_plot_position	Numeric. A number indicating which position to plot the shapefile in. The options are 1, which plots the shapefile on top of the base world map (under points and administrative boundaries), 2 which plots the shapefile on top of administrative boundaries (but under points), and 3, which plots the shapefile on top of everything.
raster_plot_position	Numeric. A number indicating which position to plot the shapefile in. The options are 1, which plots the raster on top of the base world map (under points and administrative boundaries), 2 which plots the raster on top of administrative boundaries (but under points), and 3, which plots the raster on top of everything.
shapefile_col	Character. A color or color vector indicating the color to fill the shapefile(s) with. Similar to group_col, shapefiles will be colored alphabetically.
shapefile_outline_col	Character. A color indicating the outline color of the shapefile.
shp_outwidth	Numeric. The width of the shapefile outline.
raster_col	Character. A character vector indicating the colors used to visualize the raster. The function will separate your raster data into the same number of bins as there are colors. If you provide 5 colors, for example, there will be 5 bins.
interpolate_raster	Boolean. Whether or not to interpolate the raster. The default is to interpolate the raster.
raster_breaks	Numeric or Character vector. Values to be used as breaks for the raster surface.
discrete_raster	Boolean. Indicating whether or not the raster being supplied is discrete.

Value

A ggplot object.

Author(s)

Keaka Farleigh

Examples

```
data("HornedLizard_Pop")
Test <- Plot_coordinates(HornedLizard_Pop)
```

Point_map

A function to map statistics as colored points on a map.

Description

A function to map statistics as colored points on a map.

Usage

```

Point_map(
  dat,
  statistic,
  size = 3,
  breaks = NULL,
  col,
  out.col = NULL,
  Lat_buffer = 1,
  Long_buffer = 1,
  Latitude_col = NULL,
  Longitude_col = NULL,
  country_code = NULL,
  shapefile = NULL,
  raster = NULL,
  legend_pos = "none",
  scale_bar = FALSE,
  north_arrow = FALSE,
  north_arrow_style = ggspatial::north_arrow_nautical(),
  north_arrow_position = NULL,
  shapefile_plot_position = NULL,
  raster_plot_position = NULL,
  shapefile_col = NULL,
  shapefile_outline_col = NULL,
  shp_outwidth = 1,
  raster_col = c("#2c7bb6", "#abd9e9", "#ffffbf", "#fdae61", "#d7191c"),
  interpolate_raster = NULL,
  raster_breaks = NULL,
  discrete_raster = NULL
)

```

Arguments

<code>dat</code>	Data frame or character string that supplies the input data. If it is a character string, the file should be a csv. The first column should be the statistic to be plotted. The coordinates of each row should be indicated by columns named Longitude and Latitude. Alternatively, see the Longitude_col and Latitude_col arguments.
<code>statistic</code>	Character string. The statistic to be plotted.
<code>size</code>	Numeric. The size of the points to plot.
<code>breaks</code>	Numeric. The breaks used to generate the color ramp when plotting. Users should supply 3 values if custom breaks are desired.
<code>col</code>	Character vector indicating the colors you wish to use for plotting, three colors are allowed (low, mid, high). The first color will be the low color, the second the middle, the third the high.
<code>out.col</code>	Character. A color for outlining points on the map. There will be no visible outline if left as NULL.

Lat_buffer	Numeric. A buffer to customize visualization.
Long_buffer	Numeric. A buffer to customize visualization.
Latitude_col	Numeric. The number of the column indicating the latitude for each sample. If this is not null, PopGenHelpR will use this column instead of looking for the Latitude column.
Longitude_col	Numeric. The number of the column indicating the longitude for each sample. If this is not null, PopGenHelpR will use this column instead of looking for the Longitude column.
country_code	Character. A country code or vector of country codes from the R package geo-data specifying the country that you want to plot administrative borders for (e.g, US states). You can determine the correct codes using <code>geodata's country_codes</code> function.
shapefile	Character. A file name, vector of file names of a shapefile(s) to plot on the map, or a spatvector object that is compatible with the R package <code>terra</code> . This should be used in conjunction with the <code>shapefile_plot_position</code> argument.
raster	Character. A file name or a spatraster object that is compatible with the <code>terra</code> R package. This should be used in conjunction with the <code>raster_plot_position</code> argument.
legend_pos	Character. The desired position of the legend. The default is "none", which removes the legend. Other options include "left", "right", "top" or "bottom". Please see the <code>ggplot2</code> documentation for all of the legend placement options.
scale_bar	Boolean. Whether or not to add a scale bar. Note that maps with large areas or those that use unprojected spatial data (i.e., WGS 84) will generate a warning that the scale bar varies.
north_arrow	Boolean. Whether or not to add a north arrow.
north_arrow_style	Character. Which style of north arrow to add. See ggspatial documentation for more details.
north_arrow_position	Character. The position of the north arrow. See ggspatial documentation for more details.
shapefile_plot_position	Numeric. A number indicating which position to plot the shapefile in. The options are 1, which plots the shapefile on top of the base world map (under points and administrative boundaries), 2 which plots the shapefile on top of administrative boundaries (but under points), and 3, which plots the shapefile on top of everything.
raster_plot_position	Numeric. A number indicating which position to plot the raster in. The options are 1, which plots the raster on top of the base world map (under points and administrative boundaries), 2 which plots the raster on top of administrative boundaries (but under points), and 3, which plots the raster on top of everything.
shapefile_col	Character. A color or color vector indicating the color to fill the shapefile(s) with. Similar to <code>group_col</code> , shapefiles will be colored alphabetically.

shapefile_outline_col	Character. A color indicating the outline color of the shapefile.
shp_outwidth	Numeric. The width of the shapefile outline.
raster_col	Character. A character vector indicating the colors used to visualize the raster. The function will separate your raster data into the same number of bins as there are colors. If you provide 5 colors, for example, there will be 5 bins.
interpolate_raster	Boolean. Whether or not to interpolate the raster. The default is to interpolate the raster.
raster_breaks	Numeric or Character vector. Values to be used as breaks for the raster surface.
discrete_raster	Boolean. Indicating whether or not the raster being supplied is discrete.

Value

A list containing maps and the data frames used to generate them.

Author(s)

Keaka Farleigh

Examples

```
data(Het_dat)
Test <- Point_map(Het_dat, statistic = "Heterozygosity")
```

Private.alleles *A function to estimate the number of private alleles in each population.*

Description

A function to estimate the number of private alleles in each population.

Usage

```
Private.alleles(
  data,
  pops,
  write = FALSE,
  prefix = NULL,
  population_col = NULL,
  individual_col = NULL
)
```

Arguments

data	Character. String indicating the name of the vcf file or vcfR object to be used in the analysis.
pops	Character. String indicating the name of the population assignment file or dataframe containing the population assignment information for each individual in the data. This file must be in the same order as the vcf file and include columns specifying the individual and the population that individual belongs to. The first column should contain individual names and the second column should indicate the population assignment of each individual. Alternatively, you can indicate the column containing the individual and population information using the individual_col and population_col arguments.
write	Boolean. Optional argument indicating Whether or not to write the output to a file in the current working directory. This will output to files; 1) the table of private allele counts per population (named prefix_PrivateAlleles_countperpop) and 2) metadata associated with the private alleles (named prefix_PrivateAlleles_metadata). Please supply a prefix if you write files to your working directory as a best practice.
prefix	Character. Optional argument indicating a string that will be appended to file output. Please set a prefix if write is TRUE.
population_col	Numeric. Optional argument (a number) indicating the column that contains the population assignment information.
individual_col	Numeric. Optional argument (a number) indicating the column that contains the individuals (i.e., sample name) in the data.

Value

A list containing the count of private alleles in each population and the metadata for those alleles. The metadata is a list that contains the private allele and locus name for each population.

Author(s)

Keaka Farleigh

Examples

```
data("HornedLizard_Pop")
data("HornedLizard_VCF")
Test <- Private.alleles(data = HornedLizard_VCF, pops = HornedLizard_Pop, write = FALSE)
```

Q_dat	<i>A list representing a q-matrix and the locality information associated with the qmatrix</i>
-------	--

Description

List with two elements

Usage

```
data(Q_dat)
```

Format

A list with two elements:

Qmat A q-matrix with 6 columns and 30 rows, the first column lists the sample name and the remaining 5 represent the contribution a genetic cluster to that individuals ancestry

Loc_dat The locality information for each individual in the q-matrix

...

Source

Data was generated by package authors.

Examples

```
data(Q_dat)
Qmat <- Q_dat[[1]]
rownames(Qmat) <- Qmat[,1]
Loc <- Q_dat[[2]]
Test_all <- Ancestry_barchart(anc.mat = Qmat, pops = Loc, K = 5,
plot.type = 'all', col = c('#d73027', '#fc8d59', '#e0f3f8', '#91bfdb', '#4575b4'))
```

Index

* datasets

Fst_dat, [5](#)

Het_dat, [8](#)

HornedLizard_Pop, [9](#)

HornedLizard_VCF, [10](#)

Q_dat, [24](#)

Ancestry_barchart, [2](#)

Differentiation, [3](#)

Fst_dat, [5](#)

Het_dat, [8](#)

Heterozygosity, [6](#)

HornedLizard_Pop, [9](#)

HornedLizard_VCF, [10](#)

Network_map, [10](#)

Pairwise_heatmap, [13](#)

PCA, [14](#)

Piechart_map, [15](#)

Plot_coordinates, [18](#)

Point_map, [20](#)

Private.alleles, [23](#)

Q_dat, [24](#)